
FW51JA 強力工業掛密風扇



CE

- 單相電機, 電容輔助起動, 及配備三速開關制。
- E 級絕緣,內置恒溫器保護裝置。
- \bullet 220 240 V. 1 Ph, 50 Hz $_{\circ}$
- 扇葉採用鋁合金壓鑄而成。扇葉均進行嚴謹的平衡工序。
- •金屬風扇網外表經靜電噴塗處理,美觀耐用。
- •風扇搖擺角度特大,並可自行調整。
- •安全網,並配有1.5米長3芯電源線及標準掛牆配件。
- •所有銷售型號之地扇均按 IEC60335-2-80 之標準進行測試,並已領有歐盟之安全認證。
- 功率因數(Power Factor)=0.97。





性能參數表

型號 (香港規格)	型號說明	扇葉直徑 inch/mm	額定電壓 V/Ph/Hz	檔位	功率 W	轉速 RPM	風量 m³/h	噪音 dB (A)
			220-240/1/50	1檔	110	1200	5600	54
FW51JA	掛墻密網扇	20″ / 510		2檔	125	1300	6200	58
				3檔	140	1400	6800	65


噪音值是在距離風扇2米測量

產品安裝尺寸 (mm) 及維護





INSTALLATION PROCEDURE FOR WALL MOUNTING FAN



OPERATION INSTRUCTIONS

- 1. Voltage varies between countries. The local power supply must be compatible with the technical data shown on the motor data label before the fan is connected to the power source.
- 2. The plug must be inserted to an earthed socket, which complies with the Safety Regulation of the local authority.
- 3. For safety purpose, the wall fan is to be installed so that the blades are more than 2.3 metres above the floor.
- 4. For smooth oscillation of fans, a slack of 0.4m should be left when securing power cord from motor to stand tube or wall tube.(note tag on power cord).
- 5. For safety purpose, the recommended maximum height for the Pedestal unit is 1.25 meters. (Care must be taken during adjusting the height of the standing fan).
 - > Grip the rubber handle at the top of the inner tube
 - > Using the allen key provided unfasten the screws and adjust the fan to the desirable height.
 - > Tighten the screw and put the allen key back in its pocket at the rubber handle.
- 6. The fan is fitted with a 3-speed, on & off rotary switch to adjust air velocity (1-low, 2-medium, 3-high and stop/off fan operation).
- 7. Always turn off the power at the power point and remove plug when maintenance or cleaning is carried out. Failing to do so may cause electric shock or injury as the fan may activate suddenly.
- 8. When cleaning is carried out
 - > Turn off the power at the power point and remove the plug.
 - > Remove the front guard
 - > Remove the blade from the motor by loosening the blade fixing screw.
 - > Remove the rear guard.
 - > Remove dirt with a cloth moistened with lukewarm water or a household neutral detergent and wipe dry after cleaning.
 - > When re-assembling, use the reverse order of disassembling. Ensure impeller blade is secure and tight on motor shaft.
- 9. For the best performance and safety, the fan must not be used when:
 - a. Temperature is lower than -15° C or higher than $+40^{\circ}$ C.
 - b. Humidity (at 25° C) is exceeding 90%.
 - c. In a corrosive environment, such as factory producing corrosive chemical.
- 10. Never try to disassemble, service or modify the fan. This may cause fire, abnormal activation, electric shock or injury. For servicing, contact the store where you purchased the fan.
- 11. Do not operate the fan without the blade and the guard installed. Doing so may cause injury.
- 12. Do not damage, forcibly bend, twist, pull or put a heavy object on the supply cord. Doing so may cause electric shock or a short circuit if used whilst damaged. If the supply cord is damaged, it must be replaced with a new cord by the manufacturer, its service agent or similarly qualified persons in order to avoid a hazard.
- 13. The fan motor is fitted with a thermal protection device. If a fault occurs, the fan may start and stop intermittently without warning. This may occur due to irregular power supply or excessively high ambient temperature. However if motor is faulty ,switch off immediately and return fan to the supplier or service agent.
- 14. This appliance is not intended for use by young children or infirm persons unless they have been adequately supervised by a responsible person to ensure that they can use the appliance safely.
- 15. Young children should be supervised to ensure that they do not play with the appliance.



			UV SUD
Attestation of C		Produ	ct Service
Holder of Certificate:	WING TON FAN IND 3C Kam Shing Industring 1-11 Kwai Wing Road Kowloon HONG KONG	OUSTRY LIMITED	
Product:	Fans (Stand Fan / Wall Fa	ın)	
Model(s):	FW50GA, FW51GA, FW FW50GC, FW51GC, FW FW50GE, FW51GE, FW FW50GH, FW51GH, FW FW50GV, FW51GK, FW FW50GV, FW51GV, FW FW51JA, FW51JB, FW5 FW51JR, FW51JS, FW4 FW45GB, FW46GB, FW FW45GD, FW46GD, FW FW45GV, FW46GV, FW4	250GD, FW51GD, 50GF, FW51GF, 250GJ, FW51GJ, 250GT, FW51GT, 50GW, FW51GW, 51JC, FW51JD, 25GA, FW46GA, 245GC, FW46GC, 245GE, FW46GE, 245GT, FW46GT,	
Parameters:	Rated Input :	220-240VAC, 50 Hz, See page 2 for details	
	Protection Class : Degree of Protection :	I IPX0	
Tested according to:	EN 60335-2-80:2003/A2:2009 EN 60335-1:2012/A11:2014 EN 62233:2008		
This Attestation of Conformity is is Directive 2014/35/EU relating to e limits. It confirms that the listed eq the directive and is based on the to It refers only to the particular samp overleaf.	lectrical equipment designed for uipment complies with the prine echnical specifications applicat	or use within certain voltage cipal protection requirements of ble at the time of issuance.	
Test report no.:	681101301904 - J.	TOV	
Date, 2016-11-28	(Kelvin Zeng)	732233	
declaration of conformi declaration of conformi	e necessary technical documen ty the required CE marking car ty is issued under the sole resp ctives have to be observed.	be affixed on the product. The	

Page 1 of 2

TÜV SÜD Product Service GmbH + Zertifizierstelle + Ridlerstraße 65 + 80339 München + Germany



Ref. Certif. No.

SG PSB-HS-05210

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	Fans (Stand Fan / Wall Fan)				
Name and address of the applicant	Sam Hing Cheung Fans And Equipment Limited Flat B, 1/F., Kam Shing Industrial Building 1-11 Kwai Wing Road Kwai Chung HONG KONG				
Name and address of the manufacturer	Sam Hing Cheung Fans And Equipment Limited Flat B, 1/F., Kam Shing Industrial Building, 1-11 Kwai Wing Road, Kwai Chung, HONG KONG				
Name and address of the factory	FOSHAN SHUNDE SAM HING CHEUNG FANS AND EQUIPMENT LIMITED No.1 Building, No.1 Road Guangda Market, Leiliu Town, Shunde District, 528322 Foshan, PEOPLE'S REPUBLIC OF CHINA				
Ratings and principal characteristics	Rated Input : 220-240VAC, 50 Hz, See test report for details Protection Class : I Degree of Protection : IPX0				
Model/type Ref.	FW50GA, FW51GA, FW50GB, FW51GB, FW50GC, FW51GC, FW50GD, FW51GD, FW50GE, FW51GE, FW50GF, FW51GF, FW50GH, FW51GH, FW50GJ, FW51GJ, FW50GK, FW51GK, FW50GT, FW51GT, FW50GV, FW51GV, FW50GW, FW51GW, FS50GA, FS51GA, FS50GB, FS51GB, FS50GC, FW51JA, FW51JB, FW51JC, FW51JD, FW51JR, FW51JS, FS51JA, FS51JB, FS51JC, FW45GA, FW46GA, FW45GB, FW46GB, FW45GC, FW46GC, FW45GD, FW46GD, FW45GE, FW46GE, FW45GH, FW46GH, FW45GT, FW46GT, FW45GV, FW46GV, FW45GW, FW46GW, FS45GA, FS46GA, FS45GB, FS46GB				
A sample of the product was tested and found to be in conformity with	IEC 60335-1:2010 IEC 60335-1:2010/AMD1:2013 IEC 60335-1:2010/AMD2:2016 IEC 60335-2-80:2015				
as shown in the Test Report Ref. No. which forms part of this certificate	211-700452-000				
This CB Test Certificate is issued by the National Ce	ertification Body				
CBS 072582 0032 Rev. 00 Date, 2019-06-26	liz				
Page 1 of 2 (Shaochang Liu) TÜV SÜD PSB Pte Ltd • 1 Science Park Drive • Singapore 118221 PSB Singapore					

